

FORM PTO-1390 U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371	ATTORNEY'S DOCKET NUMBER: 01P077
	U.S. APPLN. NO. (If known, see 37 CFR 1.53) 09/868333

INTERNATIONAL APPLICATION NO.: PCT/AU99/01121	INTERNATIONAL FILING DATE: 17 DECEMBER 1999	PRIORITY DATE CLAIMED: 18 DECEMBER 1998
--	--	--

TITLE OF INVENTION: FILTER CARTRIDGE AND PROCESS

APPLICANT(S) FOR DO/EO/US: Josef WINTER and Harold Thomas KRELLE

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☒ This express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1).
4. ☒ A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2))
 - a. ☒ is transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☒ has been transmitted by the International Bureau. (see attached copy of PCT/IB/308)
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☐ A translation of the International Application into English (35 U.S.C. 371(c)(2)).
7. ☐ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3)).
 - a. ☐ are transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☐ have been transmitted by the International Bureau.
 - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
 - d. ☐ have not been made and will not be made.
8. ☐ A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. ☒ An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).
10. ☐ A translation of the annexes of the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).
- Item 11. to 16. below concern document(s) or information included:
 11. ☐ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
 12. ☒ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
 13. ☒ A **FIRST** preliminary amendment.
 - ☐ A **SECOND** or **SUBSEQUENT** preliminary amendment.
 14. ☐ A substitute specification.
 15. ☐ A change of power of attorney and/or address letter.
 16. ☒ Other items or information:

International Search Report
PCT/IB/308
PCT/IPEA/409
Abstract of the Disclosure on a Separate Sheet
Application Data Sheet

U.S. APPLICATION NO. 091 868333 <small>(If known, see 37 CFR 1.51)</small>		INTERNATIONAL APPLICATION NO. PCT/AU99/01121		ATTORNEY'S DOCKET NO. 01P077	
17. <input checked="" type="checkbox"/> The following fees are submitted:				CALCULATIONS PTO USE ONLY	
BASIC NATIONAL FEE (37 CFR 1.492(a)(1)-(5)): Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO \$ 1,000.00 International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO \$ 860.00 International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO \$ 710.00 International preliminary examination fee (37 CFR 1.482) paid to USPTO but all claims did not satisfy provisions of PCT Article 33(1)-(4) \$ 690.00 International preliminary examination fee (37 CFR 1.482) paid to USPTO and all claims satisfied provisions of PCT Article 33(1)-(4) \$ 100.00					
ENTER APPROPRIATE BASIC FEE AMOUNT =				\$ 1,000.00	
Surcharge of \$130.00 for furnishing the oath or declaration later than months from the earliest claimed priority date (37 CFR 1.492(e)).				\$	
CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE	\$	
Total claims	24 - 20 =	4	X \$18.00	\$ 72.00	
Independent claims	4 - 3 =	1	X \$80.00	\$ 80.00	
MULTIPLE DEPENDENT CLAIMS(S) (if applicable)			+ \$270.00	\$	
TOTAL OF ABOVE CALCULATIONS =				\$ 1,152.00	
Reduction of 1/2 for filing by small entity, if applicable. Applicant claims Small Entity Status under 37 CFR 1.27.				\$ 576.00	
SUBTOTAL =				\$ 576.00	
Processing fee of \$130 for furnishing the English translation later than months from the earliest claimed priority date (37 CFR 1.49(f)).				\$	
TOTAL NATIONAL FEE =				\$ 576.00	
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property				\$ 40.00	
TOTAL FEES ENCLOSED =				\$ 616.00	
				Amount to be refunded:	
				charged:	
a.	<input checked="" type="checkbox"/>	A check in the amount of \$ 616.00 to cover the above fees is enclosed.			
b.	<input type="checkbox"/>	Please charge my Deposit Account No. 25-0120 in the amount of \$ to cover the above fees. A duplicate copy of this sheet is enclosed.			
c.	<input checked="" type="checkbox"/>	The Commissioner is hereby authorized to charge any additional fees which may be required by 37 CFR 1.16 and 1.17, or credit any overpayment to Deposit Account No. 25-0120 . A duplicate copy of this sheet is enclosed.			
SEND ALL CORRESPONDENCE TO Customer No. 000466 YOUNG & THOMPSON 745 South 23rd Street 2nd Floor Arlington, VA 22202 (703) 521-2297 facsimile (703) 685-0573					
June 18, 2001			By <u>Benoît Castel</u> Benoît Castel Attorney for Applicants Registration No. 35,041		

09/868333

JC03 Rec'd PCT/PTC 18 JUN 2001
PATENTS

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of

Josef WINTER et al.

Serial No. (unknown)

Filed herewith

FILTER CARTRIDGE AND PROCESS

PRELIMINARY AMENDMENT

Commissioner for Patents

Washington, D.C. 20231

Sir:

Prior to the calculation of the filing fee, please substitute Claims 1-25 as originally filed, with Claims 1-25 as filed in the Article 34 amendment of October 18, 2000. The pages containing Claims 1-25 are marked "AMENDED SHEET" and are attached hereto. Following the insertion of Claims 1-25, please amend these claims as follows:

IN THE CLAIMS:

Cancel claim 25.

Amend claim 3 as follows:

--3. (Amended) A method according to claim 1 wherein the tube shaped void includes a void forming a transverse base across one end of the tube at the free end of the male mould member, during production while the moulding material covers the free end of the male mould member, the inside of the base is vented through the male

09/868333.061801

Josef WINTER et al.

mould member to avoid suction that may inhibit pushing of the tube off the male mould member.--

R E M A R K S

The above changes in the claims merely place this national phase application in the same condition as it was during Chapter II of the international phase, with the multiple dependencies being removed. Following entry of this amendment by substitution of the pages, only claims 1-24 remain pending in this application.

Attached hereto is a marked-up version of the changes made to the claims by the current amendment. The attached page is captioned "VERSION WITH MARKINGS TO SHOW CHANGES MADE".

Respectfully submitted,

YOUNG & THOMPSON

By

Benoît Castel

Benoît Castel
Attorney for Applicants
Registration No. 35, 041
Customer No. 00466
745 South 23rd Street
Arlington, VA 22202
Telephone: 703/521-2297

June 18, 2001

Josef WINTER et al.

VERSION WITH MARKINGS TO SHOW CHANGES MADE

The claim has been amended as follows:

3. (Amended) A method according to claim 1 ~~or claim 2~~ wherein the tube shaped void includes a void forming a transverse base across one end of the tube at the free end of the male mould member, during production while the moulding material covers the free end of the male mould member, the inside of the base is vented through the male mould member to avoid suction that may inhibit pushing of the tube off the male mould member.

0986333-061804
"08190" EEE33360

0968337051

An injection moulding assembly includes a male moulding member surrounded by a female moulding member forming a void between them that upon injection of molten plastics into the mould a container can be formed. The moulding assembly includes a guide rod and ejection flange and a pair of ejection flange guide rods, an air vent valve and an injection passage. The male member includes in this embodiment eight grooves unevenly spaced so that the partially hardened container formed in the injection mould can be pushed from the mould using the ejection flange while the container is sufficiently green to enable the ribs formed in the grooves to move over the surface of the male mould during the ejection process.

A FILTER CARTRIDGE AND PROCESSFIELD OF THE INVENTION

THIS INVENTION relates to filtration and in particular but not limited to filtration of engine, transmission and hydraulic oils, fuel and solvents.

BACKGROUND ART

Oil filtration involves the use of full flow filters that filter all oil on every pass through the filter and the use of by-pass oil filters in conjunction with the full flow filters. By-pass oil filters operate in parallel with the full flow filter and generally speaking have a greater filtration than the full flow filter.

Full flow elements filter all oil on every pass and work using an element operating like a series of small sieves, with tiny holes allowing oil to pass through, while filtering out particles too large to pass through the sieve-like element. However, the holes are not small enough to filter out many finer particles, and it is these particles that can cause significant engine wear over a period of time.

On the other hand a by-pass filter operates in parallel with the full flow filter and can be much finer to progressively remove finer contaminants not captured by the full flow filter. The use of a by-pass filter progressively filters all the oil, thus increasing the useful life of the oil and reducing engine wear.

Typical by-pass oil filters include pleated element by-pass elements. These filters employ a longitudinally pleated membrane that is prone to become clogged after just a few hours work. Many by-pass filters have a pressure release valve that opens when this occurs. Another type of by-pass filter is a multiple disc by-pass filter which lasts much longer than the pleated elements.

The most effective by-pass filters employ a roll of paper wound on a central core with the feedstock being forced edgewise through the roll of paper to progress longitudinally the full width of the paper media. The filtrate then flows to the central core where it exits the filter via a return pipe. The principle of operation of this type of filter is different to the sieve-like filter and the pleated filter in so far as the paper roll filter relies on oil passing between the layers of paper, instead of passing through a sieve-like element.

Early forms of paper roll filters employed a toilet roll fitted within a filter housing. Later more sophisticated forms employed a filter element comprising a disposable canister holding the paper roll.

Australian patent number 650176 describes a filter element of the cartridge type employing a filter housing with a filter element within the housing. The filter element employs a metal canister with a paper roll forced into the canister under pressure, the canister being open at one end, for entry of feedstock, with a base at the other end, the base having a central hole for the return pipe. A layer of gauze in the base of the canister allows the filtrate to flow across the base to the return pipe in the central core. The sides of the canister are ribbed to inhibit feed stock tracking down the sides of the canister. The canister also has three or four depressions circumferentially spaced depressions in the base to hold the gauze layer away from the base providing clear secondary flow passages below the gauze to improve flow of filtrate.

The paper is tightly wound providing a much finer effective filter than the pleated and disc type filters.

Nevertheless the metal canister has a number of disadvantages. The ribbed side wall is employed to inhibit tracking of feedstock down the side wall outside the filter media but limits the density of the media. While ribbing is effective to limit tracking the canister is prone to buckle under load while the paper is being pressed into the canister. This effectively limits the amount of sideways compression that can be applied to the paper roll to a maximum defined by the flex in the side walls of the can and the inherent flexing of the ribs as the paper is being pushed into position, the limit being canister failure.

The element construction of Australian patent number 650176 results in a five percent (5%) failure rate of canisters during insertion of the paper roll into the canisters. Also the canisters are prone to be crushed by oil pressure when in use particularly at cold start up when the oil is most viscous. Construction of canisters from thicker metal would make filters more expensive and the ribbing to prevent tracking more difficult to produce in a technical sense.

Since the metal canisters are disposable they must be designed for single use application at a reasonably economical cost. It would be desirable to provide an alternative that is competitively priced, improves filtration and is less likely to buckle under load.

As an alternative to metal canisters PCT/AU96/00762 describes a plastics filter canister suitable for repeated use to enable recycling of the canister. The canister is made sufficiently rigid such that the spent paper roll can be removed using a tool and a fresh roll inserted into the canister. Due to the construction of the metal canisters of patent number 650176 efforts to remove the spent rolls from the metal canisters would in most cases render the metal canisters unusable having been designed for use as a disposable element. The problem with the canister described in PCT/AU96/00762 is that the design is not amenable to mass production using injection moulding techniques. In addition, the base of the canister was designed with closely spaced concentric rings in an effort to reproduce the effect of the secondary flow through passages utilised in the base of the metal canister while supporting the media. While this arrangement was effective in supporting the filter media and gauze the flow characteristics were less than desirable.

OUTLINE OF THE INVENTION

The present invention achieves its objectives to provide an improved disposable or reusable canister by providing a rigid plastics canister holding a roll of filter paper under higher sideways compression than known in the prior art while enabling manufacture of the filter canister as a one piece injection moulded canister.

In one aspect therefore the present invention resides in a method for construction of an internally ribbed injection moulded hollow tube section suitable for use in a filter element holding a paper roll filter media, the method comprising the steps of:

- (i) providing a generally cylindrical male mould member having longitudinally spaced rib defining grooves;

(ii) providing a female mould member adapted to overlay the male mould member in closely spaced relation defining a tube shaped void between the mould members;

5 (iii) injecting moulding material into the void, said moulding material being selected to provide a substantially rigid tube when cured;

(iv) removing the female mould member from the male mould member while the tube is in a green state, the grooves in the male mould member retaining the tube in position on the male mould member; and

10 (v) subsequently forcing the tube from the male mould member while the tube is still in a green state.

The term "green state" is used herein to mean a condition of hardening whereby the dimensions of the grooves and the degree of hardening of the tube is such that the moulded tube ribs can be pushed from the grooves in the male member without significant distortion of the tube compared to a higher degree of
15 hardening whereby the grooves serve to retain the tube on the male member.

The timing of the release of the tube from the male member will depend upon the nature and characteristics of the plastics moulding material used.

It is desirable that the grooves are not uniformly spaced on the male member so that once the initial release of the tube from all the grooves at the first instance
20 takes place as the tube is slid over the male member, the ribs do not all encounter grooves at the same time. Thus, due to the selected uneven spacing of the grooves, the force required to push the tube over the grooves is restricted such that as the tube is pushed off less than the full complement of ribs engage the grooves at any one time during the process whereby the tube is pushed from the male member.

25 The tube can be open ended or can have one end closed. The tube typically has open ends when it is intended to form an outer casing for a double ended filter such as a fuel filter.

Where the mould includes a void at the free end of the male member for forming a transverse base across one end of the tube, during production and while
30 the moulding material covers the free end of the male member it is preferable to

vent the inside of the base through the male member to avoid suction that may inhibit the pushing of the tube off the male member.

In another aspect the invention resides in a rigid injection moulded generally cylindrical canister, the canister having a side wall, the side wall having an outer surface and an inner surface, the canister being used as a filter element holding a paper roll as filter media, the canister having a thin side wall and there being spaced anti-tracking ribs projecting from the inner surface of the side wall and projecting a distance sufficient to enable the canister to be removed from a male mould member defining said ribs, the paper roll being of marginally greater diameter than the internal diameter of the canister, the canister being sufficiently rigid and the paper roll being sufficiently tightly wound that the paper roll when inserted into the canister using a press is substantially compressed to the internal dimensions of the canister without distortion of the canister.

Typically, the assembled filter element is employed in a standard filter housing where the external dimensions of the element is about 110mm in diameter and 170mm long, the applicant has found that using 17gsm thick paper and paper a paper density above about 15m/cm radial width reduces flow to undesirable levels whereas densities of about 13m/cm radial width is optimum for maximising filtration but at the same time maintaining desirable flow rates, densities below about 11m/cm radial width the roll tends to collapse within the canister base flow can become blocked and the anti-tracking ribs become ineffective. Although filters do work for a short time at these lower densities effective and reliable filtration generally occurs above about 12m/radial cm. The present invention in this preferred form enables just the right amount of paper, matched to the rib size and most desirable compression suited to injection moulding and reliable in operation when compared to the prior art.

Preferably the side walls of the canister include marginal flaring of at least one end of the canister so that the side wall of the canister is medially biased of the order of .5 to 1 millimetre so that the side wall of the canister is biased inwardly to resist distortion of the side wall and enhance compression of the paper roll inside

the canister. Typically the flared end is the open end at which the paper roll is pushed into the canister.

Preferably the ribs project 1 millimetre to 2 millimetres from the inner surface of the canister with 1.5 millimetres being optimum. Where the ribs are evenly spaced it is preferable that they be at the shallower end of the range of projection, the inner wall may have a slight taper on the inner surface to further assist release from the male mould. However, the paper must be more tightly wound and placed under higher compression to achieve the same filter efficiency and anti-tracking when compared to a cylindrical shape where the inner diameter is uniform or carries the medially biased inward shape.

The canister preferably includes a marginal taper on the inner surface at the open end to act as a lead in for the paper roll, the objective being to minimise the "give" in the canister and to maximise the sideways compression applied to the shallow anti-tracking ribs.

Preferably where the canister has a base, the base includes external radial strengthening ribs and again is biased inwardly. The base is typically inwardly dished by up to 2 millimetres at the centre relative to the edges in order to provide a bias against the loading of the paper roll as the paper roll is being pressed home into the canister.

The base preferably has an inner surface with radially extending flow passages separated by lands, the lands defining supporting surfaces for a gauze to evenly distribute and support the paper roll media across the base of the canister and to provide secondary flow passages across the base of the canister below the gauze.

BRIEF DESCRIPTION OF THE DRAWINGS

In order that the present invention can be more readily understood and be put into practical effect reference will now be made to the accompanying drawings which illustrate preferred embodiments of the invention and wherein:

Figure 1 is a drawing illustrating an injection moulding apparatus for implementing the method described;

Figures 2, 3 and 4 are schematic drawings illustrating the moulding process utilising the apparatus of Figure 1;

Figures 5 and 6 are opposite perspective views; Figure 7 is a top view; Figure 8 is a bottom view; and Figure 9 is a cross-section all illustrating a canister made using the apparatus of Figure 1;

Figure 10 is a perspective drawing illustrating a hydraulic press used to push a paper roll into the canister of Figures 5 to 9;

Figure 11 is a schematic drawing illustrating operation of the press and the assembly of an oil filter element;

Figure 12 is a schematic drawing of the hydraulic circuit for the press; and Figure 13 is a section through a fuel filter element.

METHOD OF PERFORMANCE

Referring to the drawings and initially to Figure 1 there is illustrated an injection moulding assembly 10 comprising a male moulding member 11 surrounded by a female moulding member 12 forming a void 13 between them that upon injection of molten plastics into the mould a container can be formed. The moulding assembly includes a guide rod 14 and ejection flange 16 and a pair of ejection flange guide rods 17 and 18, an air vent valve 15 and an injection passage 19. The male member 11 includes in this embodiment eight grooves 20 unevenly spaced so that the partially hardened container formed in the injection mould can be pushed from the mould using the ejection flange 16 while the container is sufficiently green to enable the ribs formed in the grooves 20 to move over the surface of the male mould 11 during the ejection process.

Figures 2, 3 and 4 illustrate the three stages of production of a container using the injecting moulding assembly of Figure 1. Figure 2 represents the first stage in the process whereby liquid plastic is forced in under pressure and is represented as the black section at 21. An air vent valve at 15 is closed and the female moulding member 12 is in the closed position along the main guide rails 22.

In stage 2 represented by Figure 3 the female mould member 12 has been withdrawn while the container 23 remains on the male moulding member. The container 23 is still green at this stage. In the third stage of the process the ejection

flange 16 is driven along the surface of the male mould member and the air vent valving is opened and the container 23 is pushed off the male moulding member 11 as illustrated in Figure 4.

A typical container formed using the apparatus of Figure 1 is illustrated in Figures 5 to 9. The container is a generally cylindrical canister having a side wall 24, the side wall having an outer surface 25 and an inner surface 26, the canister being used as a filter element holding a paper roll as filter media, the canister has a thin side wall and includes spaced anti-tracking ribs 27 that project in this case 1.5 millimetres into the interior of the container. The base 28 is inwardly dished at 29 and also includes a curved seat 30 for a sealing washer, a single aperture 31 being provided for a return tube for returning the filtrate from the filter to the main oil or fuel circuit. The base is externally ribbed with strengthening ribs 32 while the interior of the base includes radial flow passages 33 separated by lands 34. As can be seen there are in this embodiment 18 flow passages 33 and an annular projection 35. The annular projection 35 also serves an anti-tracking purpose in so far as any small amounts of oil that begin to track down the sides of the container become trapped in the annular channel 36 around the base 28 of the canister. The container 23 includes a flared marginal edge region at 36 and an outward chamfer at 37 which operates as a lead in for the paper roll into the canister 23.

Figure 10 illustrates the operation of a press 38 employing a hydraulic ram 39 having a cylinder assembly 40 with a piston rod 41 and a platen 42 and a base platen 43 with a control valve 44.

Assembly of a filter element is illustrated in Figure 11. The diameters illustrated with the arrows 45 and 46 are approximately the same with the paper roll 47 comprising approximately 43 metres of paper wound into a tight 110 millimetre to 114 millimetre diameter roll on a cardboard core.

A layer of gauze 49 is placed in the base of the canister 23, the paper is initially pushed into position by hand as illustrated in Figure 11 and then the guiding platen 42 is placed down onto the paper roll, activation of the hydraulic cylinder assembly causes the paper roll to be pushed into the canister 23.

The press used to force the paper roll into the canister in one typical embodiment is a 50 millimetre diameter hydraulic cylinder assembly 39. A one horse power single phase electric motor drives a 20 litre per minute gear pump 50. The cylinder operating pressure is 70 to 80 pounds per square inch which is achieved through an in-built adjustable relief valve 51. The relief valve is situated at the directional spool valve that the operator uses to operate the cylinder 52.

Other elements illustrated in the hydraulic circuit is the hydraulic reservoir 53 and a pressure valve 54 and a filter 55.

The last drawing illustrates application of the present invention to a fuel filter element 56 which can be made using the apparatus of Figure 1 simply by adjusting the thickness of the base to be very thin so that the base can be removed making an open ended tube. Fuel to be filtered flows into the tube from both ends. Two half size paper rolls are inserted with a return flow path provided by an intermediate gauze. A return tube is located in the central core as in the previous embodiment.

Whilst the above has been given by way of illustrative example of the present invention many variations and modifications thereto will be apparent to those skilled in the art without departing from the broad ambit and scope of the invention as herein set out in the appended claims.

09/868333

10

JCOB Rec'd PCT/FTC 18 JUN 2001

CLAIMS

1. A method of construction of internally ribbed injection moulded hollow tube sections suitable for use in a filter element holding a paper roll filter media, the method comprising steps of:

5 (i) providing a generally cylindrical male mould member having longitudinally spaced rib defining grooves and a free end;

(ii) providing a female mould member adapted to overlay the male mould member in closely spaced relation defining a tube shaped void between the mould members;

10 (iii) injecting moulding material into the void, said moulding material being selected to provide a substantially rigid tube when cured;

(iv) removing the female mould member from the male mould member while the tube is in a green state, the grooves in the male mould member retaining the tube in position on the male mould member; and

15 (v) subsequently forcing the tube from the male mould member while the tube is still in a green state.

2. A method according to claim 1 wherein the grooves are not uniformly spaced on the male mould member so that once the initial release of the tube from all of the grooves takes place, as the tube is progressively slid off the male mould member, the ribs do not all encounter grooves at the same time.

20 3. A method according to claim 1 or claim 2 wherein the tube shaped void includes a void forming a transverse base across one end of the tube at the free end of the male mould member, during production while the moulding material covers the free end of the male mould member, the inside of the base is vented through
25 the male mould member to avoid suction that may inhibit pushing of the tube off the male mould member.

4. A rigid injection moulded generally cylindrical canister formed about a male mould member, the canister having a side wall, the side wall having an outer surface and an inner surface, the canister being used as a filter element holding a
30 paper roll as filter media, the canister having a thin side wall and there being spaced anti-tracking ribs projecting from the inner surface of the side wall and

projecting a distance sufficient to enable the canister to be removed from the male mould member during a moulding process and while still sufficiently flexible, the paper roll being of marginally greater diameter than the internal diameter of the canister, the canister being sufficiently rigid and the paper roll being sufficiently tightly wound that the paper roll, when inserted into the canister using a press, is substantially compressed to the internal dimension of the canister without distortion of the canister.

5. A rigid injection moulded canister according to claim 4 wherein the ribs project at 1 mm to 2 mm from the inner surface of the canister.

10 6. A rigid injection moulded canister according to claim 4 wherein the ribs
project about 1.5 mm from the inner surface of the canister.

7. The canister according to claim 4 wherein the ribs are evenly spaced, the inner wall having slight taper on the inner surface to enable release from the male mould.

15 8. The canister according to claim 4 including a marginal taper on the inner
surface at the open end to act as a lead-in for the paper roll.

9. The canister according to claim 4 including a base and wherein the base is inwardly biased.

10. The canister according to claim 4 including a base and wherein the base is
20 inwardly dished at the centre relative to the edges in order to provide a bias against
loading as a paper roll is being pressed into the canister.

11. The canister according to claim 4 including a base and wherein the base has an inner surface with radially extending flow passages separated by lands, the lands defining a supporting surface to evenly distribute and support the paper roll media across the base of the canister to provide secondary flow passages across the base of the canister.

12. A filter element having a rigid injection moulded generally cylindrical canister formed about a male mould member, the canister having a side wall, the side wall having an outer surface and an inner surface, the canister holding a paper roll as filter media, the canister having a thin side wall and there being spaced anti-tracking ribs projecting from the inner surface of the side wall and projecting

a distance sufficient to enable the canister to be removed from the male mould member during a moulding process and while still sufficiently flexible, the paper roll being of marginally greater diameter than the internal diameter of the canister, the canister being sufficiently rigid and the paper roll being sufficiently tightly wound that the paper roll, when inserted into the canister using a press, is substantially compressed to the internal dimension of the canister without distortion of the canister.

13. A filter element according to claim 12 wherein the ribs project at 1 mm to 2 mm from the inner surface of the canister.

10 14. A filter element according to claim 12 wherein the ribs project about 1.5 mm from the inner surface of the canister.

15. A filter element according to claim 12 wherein the ribs are evenly spaced, the inner wall having slight taper on the inner surface to enable release from the male mould.

15 16. A filter element according to claim 12 including a marginal taper on the inner surface at the open end to act as a lead-in for the paper roll.

17. A filter element according to claim 12 including a base and wherein the base is inwardly biased.

18. A filter element according to claim 12 including a base and wherein the base is inwardly dished at the centre relative to the edges in order to provide a bias against loading as a paper roll is being pressed into the canister.


19. A filter element according to claim 12 including a base and wherein the base has an inner surface with radially extending flow passages separated by lands, the lands defining a supporting surface to evenly distribute and support the paper roll media across the base of the canister to provide secondary flow passages across the base of the canister.

20. A filter element according to claim 12 wherein the paper roll is wound to an average density of about 13m/radial cm.

21. A filter element according to claim 12 wherein the paper roll is wound to an average density of no less than about 11m/radial cm and no more than about 15m/radial cm.

22. A filter element according to claim 12 wherein the paper roll is wound to an average density of about 13m/radial cm.
23. A filter element according to claim 12 wherein the paper roll is wound to an average density of about 13m/radial cm and the paper thickness is about 17gsm.
- 5 24. A filter element according to claim 12 wherein the paper roll is wound to an average density of no less than about 11m/radial cm and no more than about 15m/radial cm and the paper thickness is about 17gsm.
25. A filter canister substantially as described with references to the accompanying drawings.

09868333 061801
T08190 00000000






FIG. 2

3/11




FIG.3

4/11




FIG. 4

FIG. 4




FIG. 5




FIG. 6

09868333, 061801




FIG. 7







FIG. 8

FIG. 9










FIG. 12




FIG. 13

COMBINED DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

the specification of which: *(check one)*

REGULAR OR DESIGN APPLICATION

☐ is attached hereto.

☐ was filed on _____ as application Serial No. _____ and was amended on _____ (if applicable).

PCT FILED APPLICATION ENTERING NATIONAL STAGE

☒ was described and claimed in International application No. PCT/AU99/01121 / filed on 17 December 1999 / and as amended on 18 October 2000 / (if any).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, §1.56.

PRIORITY CLAIM

I hereby claim foreign priority benefits under 35 USC 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed.

PRIOR FOREIGN APPLICATION(S)

Country	Application Number	Date of Filing (day, month, year)	Priority Claimed
Australia /	PP7840 /	18 December 1998 /	Yes

(Complete this part only if this is a continuing application.)

I hereby claim the benefit under 35 USC 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of 35 USC 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37 Code of Federal Regulations §1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application:

(Application Serial No.)

(Filing Date)

(Status--patented, pending, abandoned)

POWER OF ATTORNEY

The undersigned hereby authorizes the U.S. attorney or agent named herein to accept and follow instructions from INTELLPRO as to any action to be taken in the Patent and Trademark Office regarding this application without direct communication between the U.S. attorney or agent and the undersigned. In the event of a change in the persons from whom instructions may be taken, the U.S. attorney or agent named herein will be so notified by the undersigned.

As a named inventor, I hereby appoint the following attorney(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith: **Robert J. PATCH, Reg. No. 17,355, Andrew J. PATCH, Reg. No. 32,925, Robert F. HARGEST, Reg. No. 25,590, Benoît CASTEL, Reg. No. 35,041, Eric JENSEN, Reg. No. 37,855, and Thomas W. PERKINS, Reg. No. 33,027, c/o YOUNG & THOMPSON, Second Floor, 745 South 23rd Street, Arlington, Virginia 22202.**

Address all telephone calls to Young & Thompson at 703/521-2297.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole or first inventor: Josef WINTER
(given name, family name)

Inventor's signature [Signature] Date 16th June 2001

Residence: Shailer Park, Queensland, Australia AUX Citizenship: Australian

Post Office Address: 114 Koolan Crescent, Shailer Park, Queensland, 4128, Australia

Full name of second joint inventor, if any: Harold Thomas KRELLE
(given name, family name)

Inventor's signature [Signature] Date 16th June 2001

Residence: Sunnybank Hills, Queensland, Australia AUX Citizenship: Australian

Post Office Address: 89 Chilton Street, Sunnybank Hills, Qld, 4109, Australia

Full name of third joint inventor, if any:
(given name, family name)

Inventor's signature _____ Date _____

Residence: _____ signed in my presence by _____ Citizenship: _____

Post Office Address: _____

TIMOTHY MATTHEW O'DWYER, M.A., LL.B., J.P.
General Notary Public in the Australian State of Queensland
(appointment does not expire), Justice of the Peace
(Commissioner for Declarations) for the State of Queensland,
Solicitor of the Supreme Court of Queensland and
Solicitor of the High Court of Australia.
Contact: O'DWYER & BRADLEY SOLICITORS
Kingston Rd, Slacks Creek, Queensland, Australia
Ph: 07-3208 1488 Fax: 07-3808 4316
Email: argonautlegal@platypus.net.au

